IMPORTANT - All Service Personnel Should Read and Initial

SERVICE BULLETIN

2005MY Legacy & Outback Vehicles APPLICABILITY:

Engine Coolant System Refilling SUBJECT:

09-39-04 NUMBER:

> 05/07/04 DATE:

INTRODUCTION

The purpose of this bulletin is to address proper refilling of the engine coolant system. To prevent air pockets, an evacuation and refilling tool is required. This required tool can be obtained through Kent Moore, Snap-on or your local tool distributor. The tool creates a vacuum in the coolant system removing possible air pockets allowing for efficient refilling of the engine coolant system.

REPAIR PROCEDURES

When refilling the radiator refer to the applicable service manual for coolant recommendations and capacities. The evacuation and refilling tool comes with complete operating instructions from the manufacturer, which needs to be followed.

Note: Always use SUBARU Genuine Coolant, since other coolant may cause corrosion. SUBARU Genuine Coolant contains antifreeze and anti-rust agents, which is especially made for Subaru engines.



CAUTION: VEHICLE SERVICING PERFORMED BY UNTRAINED PERSONS COULD RESULT IN SERIOUS INJURY TO THOSE PERSONS OR TO OTHERS.

Subaru Service Bulletins are intended for use by professional technicians ONLY. They are written to inform those technicians of conditions that may occur in some vehicles, or to provide information that could assist in the proper servicing of the vehicle. Properly trained technicians have the equipment, tools, safety instructions, and know-how to do the job correctly and safely. If a condition is described, DO NOT assume that this Service Bulletin applies to your vehicle, or that your vehicle will have that condition.

